

HM-1115D26-VHLE

Features

- Adopt Intel® Tiger Lake UP3 Series processor
- Intel® Iris® Xe Graphics
- 2 x DDR4 3200MHz SO-DIMM memory, Max 32GB
- VGA/DP, 2 * EDP, 2 * HDMI support four screen display
- 2×USB3.0, 8×USB2.0
- 6×COM, 1×LPT, 1×PS/2
- 2 x RJ45 LAN (RTL8111H PCIe bus network card chip), 1 x M.2

KEY-E, 1xM.2 KEY-B, 1 x M.2 M Key, 2 x SATA

- Active fan cooling module, efficient heat dissipation, powerful system performance.
- Support Wake on LAN, diskless boot, Auto power on
- Suitable for retail, self-service, all-in-one pc, industrial control and etc.



Specification

Processor System	
CPU	Intel® Core™ i5 1135G7 4C/8T 2.4GHz 8M Max Turbo 4.20 GHz
Memory	
Slot Number	1
Type	DDR4 SO-DIMM 3200MHz
Max Size	32GB
Channels	Single Channel
Graphics	
Controller	Intel® Iris® Xe Graphics
VGA	1×Port (Choose one from two colay display port)
HDMI	2×Port,
LVDS	1×Header (colay EDP)
EDP	2×Header
Multi Display	Quad-Display
Storage	
SATA	2
M.2	1(Key-M 2230/2280 , NVME)
COM	
Port Number	1×DB9 (male pin) , 5×Header
Mode	6×RS232 , COM2 Support RS232/RS485
PWR	COM2&COM3 Support RI/5V/12V optional
Expansion Slot	
Mini-PCle	1 (Support WIFI/BT, 3G/4G)

IO & Connector	
Rear I/O	1×DC Jack
	2×HDMI (double-deck)
	1×VGA (Choose one from two colay display port)
	2×USB3.0 , 2×USB2.0(Choose one from two colay lan2)
	2×RJ45 1000M LAN(Choose one from two colay USB2.)
Internal Connector	1×Line-out, 1×Mic-in
	1×LVDS (Multiplexing with EDP2) , 2×EDP, 1×M.2 KEY-M,
	1×M.2 KEY-E,1×M.2 KEY-B, 1×SIM
	1×F_Audio, 1×JSPK
	6×JCOM
	1×JPS/2, 1×JLPT
	2×JUSB , 4 × USB2.0 port
	2×SATA, 1×M.2 Key M
	1×F_PANEL, 1×TPM, 1×JGPIO (8 in 8 out)
	1×CPU_FAN、1×SYS_FAN
	2×SATA_PWR, 1×INVERT
	1×DC_IN
Mechanical & Environment	
Dimension	170×170mm
PWR Input	DC12~19V
Operation	0~60°C, 10%~90%RH , non-condensing

Detailed specifications

HM-1115D16-VH2E	Core™ i3-1115G4 2C/4T 3.0GHz(Turbo 4.1GHz) 6MB	1×1000M LAN	10×USB(2×USB3.0)	6×COM	1×HDMI +1×VGA+2×EDP
HM-1115D26-VHLE	Core™ i3-1115G4 2C/4T 3.0GHz(Turbo 4.1GHz) 6MB	2×1000M LAN	8×USB(2×USB3.0)1	6×COM	1xHDMI+1xVGA+1xLVDS+1xEDP
HM-1135D16-VH2E	Core™ i3-1115G4 2C/4T 3.0GHz(Turbo 4.1GHz) 6MB	1×1000M LAN	0×USB(2×USB3.0)	6×COM	1×HDMI +1×VGA+2×EDP
HM-1135D26-VHLE	Core™ i5-1135G7 4C/8T 2.4GHz(Turbo 4.20 GHz) 8M	2×1000M LAN	8×USB(2×USB3.0)	6×COM	1xHDMI+1xVGA+1xLVDS+1xEDP